# AUTOBACS FULLY-SYNTHETIC EUROPEAN CAR



# Japan Quality

Developed by AUTOBACS with over 45 years automotive industry experience. AUTOBACS is the trusted name for engine protection and all your motoring needs. Let AUTOBACS engine oils enrich your driving experience with the spirit of Japanese quality and reliability.







## Fully-Synthetic European Car

### **Description**

AUTOBACS Fully-Synthetic engine oils specifically formulated to meet European motor vehicle manufacturer standards. These engine oils carry the latest European Automobile Manufacture's Association (ACEA) specification ratings for viscocity and stability. AUTOBACS Fully-Synthetic engine oil for European cars delivers superior engine protection from cold starts to high temperatures, helping to provide maximum vehicle performance.

#### **Advantages**

- Specifically formulated to meet stringent European car maker requirements
- Excellent protection for use in both gasoline and diesel engines
- Compatible with high performance passenger vehicles and light vans to extend life of DPF and TWC

## **5W-30** acea c3

Fully synthetic engine oil made in Europe and specifically formulated to meet ACEA C3 standards for European vehicles. Meets manufacturer specifications for use in Mercedes Benz, Porsche and Volkswagen where specified in the owners manual.

| Oil type                    |      | Fully-Synthetic |
|-----------------------------|------|-----------------|
| Pour point (℃)              |      | -42             |
| Flash point (℃)             |      | 231             |
| Viscosity Index             |      | 160             |
| Kinematic viscosity (mm²/s) | 40℃  | 73              |
|                             | 100℃ | 11.9            |

#### Meets Manufacturer Requirements:

- ✓ MERCEDES MB 229.51
- ✓ PORSCHE C30
- ✓ VOLKSWAGEN 504.00 / 507.00



## 5W-40 ACEA C3 / API SN

Fully synthetic engine oil made in Europe and specifically formulated to meet ACEA C3 standards for European vehicles. Meets manufacturer specifications for use in Ford, Opel, Mercedes Benz, Porsche, Renault and Volkswagen where specified in the owners manual.

|                             | _    |                 |
|-----------------------------|------|-----------------|
| Oil type                    |      | Fully-Synthetic |
| Pour point (°C)             |      | -39             |
| Flash point (°C)            |      | 224             |
| Viscosity Index             |      | 172             |
| Kinematic viscosity (mm²/s) | 40℃  | 86              |
|                             | 100℃ | 14.2            |

#### Meets Manufacturer Requirements:

- ✓ FORD WSS-M2C 917A
- ✓ OPEL Dexos 2
- ✓ MERCEDES MB 226.5 / MB 229.31
- ✓ PORSCHE A40
- ✓ RENAULT RN0700 / 0710
- ✓ VOLKSWAGEN 502.00 / 505.01





