

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 24/02/2016 Version: 3.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : **5W40 C3**Product code : HU0094

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Engine oil

Function or use category : Lubricants and additives

## 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

Autobacs France 254 ter, boulevard du Havre 95480 Pierrelaye - France Tél. : + 33(0) 1 75 72 02 60 www.autobacs.fr

#### 1.4. Emergency telephone number

France	ORFILA +33 1 45 42 59 59

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic Not classified

Full text of hazard classes and H-statements : see section 16

## 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

#### 2.3. Other hazards

No additional information available

# SECTION 3: Composition/information on ingredients

# 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	25 - 50	Asp. Tox. 1, H304

printed13/09/2018 EN (English) SDS Ref.: HU0094 1/7



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 24/02/2016 Version: 3.0

Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	5 - 20	Asp. Tox. 1, H304
Mineral oil*		1 - 10	Asp. Tox. 1, H304
bis(nonylphenyl)amine	(EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	0,1 - 2,5	Aquatic Chronic 4, H413
Calcium branched alkyl phenate sulphide (overbased)	(EC-No.) POLYMER	0,1 - 2,5	Aquatic Chronic 4, H413

<sup>\*</sup> Contains one or more of the following EC numbers: 265-157-1 / 265-169-7 / 265-158-7 / 265-159-2

Full text of H-statements: see section 16

#### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general : In all cases of doubt, or when symptoms persist, seek medical attention.

First-aid measures after inhalation : Assure fresh air breathing. If symptoms persist, call a physician.

First-aid measures after skin contact : Remove contaminated clothing. Wash with plenty of water/.... Seek medical attention if ill effect

or irritation develops.

First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes

minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Contact

ophthalmologist immediately.

First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

Immediately call a POISON CENTER/doctor. Never give anything by mouth to an unconscious

person.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Symptoms may include dizziness, headache, nausea and loss of coordination.

Symptoms/effects after skin contact : Prolonged or repeated contact with the skin may cause dermatitis. Skin rash/inflammation.

Redness. Itching.

Symptoms/effects after eye contact : May cause slight irritation. Redness. Pain.

Symptoms/effects after ingestion : Aspiration of this material may cause chemical pneumonia.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Sand. AFFF foam. Water spray. Carbon dioxide.

Unsuitable extinguishing media : Do not use water jet.

#### 5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire : On burning: release of harmful/irritant gases/vapours. Carbon oxides (CO, CO2).

Hazardous decomposition products in case of : On incomplete combustion releases : fume, Carbon monoxide, Carbon dioxide, Nitrogen

ire oxides, Sulphur oxides, Organic compounds, Aldehydes.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering

the environment. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Self-contained breathing apparatus.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Concerning personal protective equipment to use, see section 8. Wear suitable protective

clothing and gloves.

Emergency procedures : Evacuate unnecessary personnel. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Provide adequate ventilation.

# 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves. Avoid breathing Aerosols, Vapours. Equip

cleanup crew with proper protection.

Emergency procedures : Ventilate area. Clean up any spills as soon as possible, using an absorbent material to collect

it. Stop leak if safe to do so.

printed13/09/2018 EN (English) SDS Ref.: HU0094 2/7



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 24/02/2016 Version: 3.0

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Collect all

waste in suitable and labelled containers and dispose according to local legislation.

Other information : May be dangerously slippery if spilled.

#### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. For disposal of residues refer to section 13: Disposal considerations" ".

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Keep away from

sources of ignition - No smoking. Do not get in eyes, on skin, or on clothing. Do not eat, drink or

smoke in areas where product is used.

Hygiene measures : Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using

this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with skin, eyes and clothing.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep away from sources of ignition - No smoking. Store in original container. Store in a dry,

well ventilated place away from sources of heat, ignition and direct sunlight. Keep container

tightly closed. Keep container closed when not in use.

Heat and ignition sources : No flames, no sparks. Eliminate all sources of ignition.

Information on mixed storage : Oxidation agents.

Storage area : Store away from heat. Floors should be impervious, resistant to liquids and easy to clean.

Special rules on packaging : Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Materials for protective clothing : Separate working clothes from town clothes. Launder separately

Hand protection : Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to

European standard NF EN 374 or equivalent). Time of penetration is to be checked with the

glove producer

Eye protection : Eye protection, including both chemical splash goggles and face shield, must be worn when

possibility exists for eye contact due to spraying liquid or airborne particles

Skin and body protection : Wear suitable protective clothing

Respiratory protection : Avoid the formation of mists in the atmosphere. Where exposure through inhalation may occur

from use, respiratory protection equipment is recommended. respirator with combination filter

for vapour/particles

Other information : Provide local exhaust or general room ventilation to minimize mist and/or vapour

concentrations.

#### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : amber.

Odour Colour : characteristic.

Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available

Melting point : -39 (≤ -36) °C [Pour Point - ASTM D 5950]

Freezing point : No data available

printed13/09/2018 EN (English) SDS Ref.: HU0094 3/7



## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 24/02/2016 Version: 3.0

Boiling point : No data available

Flash point : > 180 °C

Auto-ignition temperature · No data available Decomposition temperature No data available Flammability (solid, gas) No data available Vapour pressure No data available Relative vapour density at 20 °C : No data available Relative density : 0,852 [D 20/4] Solubility : No data available Log Pow : No data available

Viscosity, kinematic : 86 cSt (40 °C) | 14,2 (100 °C) [ASTM D 7279]

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

#### 9.2. Other information

No additional information available

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

No additional information available

#### 10.4. Conditions to avoid

All heat sources, including direct sunlight. Sparks. Open flame.

#### 10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

No additional information available

his/nonvlnhenyl)amine

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	> 5000 mg/m³ (4h) (OECD 403 method)

Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

rotatively large proportion of catalat	
LD50 oral rat	> 5000 mg/kg (OECD 420 method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h (mg/L air, aerosol) (OECD 403 method)

bio(non-yiphonyi)ammo		
LD50 oral rat	> 5000 mg/kg (OECD 401 method)	
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)	

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

printed13/09/2018 EN (English) SDS Ref.: HU0094 4/7



## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 24/02/2016 Version: 3.0

STOT-single exposure : Not classified STOT-repeated exposure : Not classified : Not classified : Not classified

Aspiration hazard : Not classified

5W40 C3

Viscosity, kinematic 86 mm²/s (40 °C) | 14,2 (100 °C) [ASTM D 7279]

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Calcium branched alkyl phenate sulphide (overbased)	
LC50 fish 1	> 1000 mg/l (Pimephales promelas, 96h)
EC50 other aquatic organisms 1	> 1000 mg/l (Cladocère, 48h)
ErC50 (algae)	> 1000 mg/l (algues vertes, 96h)

Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)
EC50 Daphnia 1	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)
EC50 Daphnia 2	> 10000 mg/l (Daphnia magna, 48h) (OECD 202 method)
NOEC (acute)	>= 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)
NOEC chronic fish >= 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox, 14/28d)	
NOEC chronic crustacea	10 mg/l (Daphnia magna, 21d) (OECD 211 method)

Mineral oil*	
LC50 fish 1	> 100 mg/l (Pimephales promelas, 4 DY)
EC50 Daphnia 1	> 10000 mg/l (Cladocère; 2 DY)
ErC50 (algae)	> 100 mg/l (Algue verte, 3jrs)
NOEC chronic crustacea	> 10 mg/l (Cladocère, 21 DY)

bis(nonylphenyl)amine	
LC50 fish 1	120 mg/l (Danio rerio, 96h, OECD 203)
EC50 Daphnia 1 120 mg/l (Daphnia magna, 48h, OECD 202)	
ErC50 (algae)	120 mg/l (Desmodesmus subpicatus, 72h, OECD 201)

# 12.2. Persistence and degradability

	Distillates (petroleum), nydrotreated neavy	paraπinic (64/42-54-/)
ı		

Persistence and degradability Inherently biodegradable.

Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

Biodegradation 31 % (28d) (OECD 301F method)

Mineral oil\*

Biodegradation 31 % (28DY; OECD TG 301 B)

bis(nonylphenyl)amine

Persistence and degradability Not readily biodegradable.

Biodegradation 1 % Sturm (28d)

#### 12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Bioaccumulative potential	Potentially bioaccumulable.
Calcium branched alkyl phenate sulphide (overbased)	
Log Kow	10,88
bis(nonylphenyl)amine	
Log Pow	> 7,6
Log Kow 7.3 Octanol /water coefficient (0.1d)	

#### 12.4. Mobility in soil

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Ecology - soil	Floats on water. Insoluble in water.

printed13/09/2018 EN (English) SDS Ref.: HU0094 5/7



## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 24/02/2016 Version: 3.0

bis(nonylphenyl)amine	
Ecology - soil	Product adsorbs little onto the soil.

#### 12.5. Results of PBT and vPvB assessment

Component	
bis(nonylphenyl)amine ()	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

European List of Waste (LoW) code : 13 02 00 - waste engine, gear and lubricating oils

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID	
14.1. UN number					
No dangerous good in sense of transport regulations.(ADR, RID, IMDG, IATA)					
14.2. UN proper shippin	14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard class(es)					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards					
Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	
environment : No	environment : No	environment : No	environment : No	environment : No	
	Marine pollutant : No				
No supplementary information available					

## 14.6. Special precautions for user

#### - Overland transport

No data available

#### - Transport by sea

No data available

#### - Air transport

No data available

## - Inland waterway transport

Carriage prohibited (ADN) : No Not subject to ADN : No

- Rail transport

Carriage prohibited (RID) : No

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

printed13/09/2018 EN (English) SDS Ref.: HU0094 6/7



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 24/02/2016 Version: 3.0

## 15.2. Chemical safety assessment

No additional information available

# **SECTION 16: Other information**

#### Indication of changes:

	Revision date	Modified	
2.2	EUH-statements	Removed	
3.2	Composition/informatio n on ingredients	Modified	
4.2	Symptoms/effects after skin contact	Modified	

Training advice

: Not to be used for any purpose other than the one the product was designed for.

#### Full text of H- and EUH-statements:

Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Aquatic Chronic Not classified	Hazardous to the aquatic environment - Chronic Hazard Not classified
Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aquatic Chronic Not classified Expert judgment

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

printed13/09/2018 EN (English) SDS Ref.: HU0094 7/7